

FP503. The smallest and powerful pneumatic scissor as ever.



WHAT'S NEW:

Central back-located air exhaust Strengthened structure for hard materials New integrated sharpening device High manageability in 800 g

RASOR ELETTROMECCANICA SRL

Via Vincenzo Caldesi 6 ● 20161 Milan · Italy ph. +39 02 66 22 12 31 ● fax +39 02 66 22 12 93 info@rasor-cutters.com

www.rasor-cutters.com



TECHNICAL DETAILS:

Muffled turbine motor with central back-located air exhaust 6 bar nominal* (± 1 bar) lubricated air supply

Air consumption: 9 std liters/sec*

Power: 350 W at nominal air supply conditions **Blade:** 50 mm with hard metal counterblade

Blade descr.: 503EHSS, 50 mm dia., 6-edge, HSS steel

Blade speed: 1900 r.p.m.*

Cutting ability: up to 9 mm

Sound pressure: 72 dBe (EN ISO 15744)*
Vibration Level: 1,36 m/sec2 (ISO 8662)*

Net weight: 800 g

Total weight (with packing): 1630 g

Temperature range: $0 - 55 \, \text{C}$

Umidity range: 10 - 95% without condensate

^{*}The reported data are collected at a pressure of 6 bar (ISO 2787: 1984), reccomended operating pressure.